

RLH Rhino Commercial - Load Holders (Pr)


Place these instructions in the vehicle's glove box after installation is complete.

Important: Please read these instructions carefully prior to installation. Please refer to your fitting instruction to ensure that the roof racks are installed in the correct locations.

Important: Check the contents of kit before commencing fitment and report any discrepancies.


Parts List


Item	Component Name	Qty.	Part No.
1	M10 x 25mm Hex Bolt	2	B071
2	M10 Shake Proof Washer	2	W021
3	M10 x 30mm Flat Washer	2	W023
4	Load Holder	2	M005
5	M10 Channel Nut	2	N024
6	Fitting Instruction	1	RR11



Remove the rubber buffer strip from the crossbar. Loosen the channel nut and slide the load holder T shaped section into the top recess of the Rhino crossbar.

Position the load holder, turn the attachment bolt so that the channel nut rotates and locates across the crossbar, tighten. Trim rubber buffer strip to suit.





Rhino-Rack 3 Pike Street, Rydalmere, NSW 2116, Australia. (Ph) (02) 9638 4744 (Fax) (02) 9638 4822

Prepared By: Sheila Oliveira Authorised By: Gary England Document No: RR-11 Issue No: 03 Issue Date: 27/05/2003

These instructions remain the property of Fetovu Pty Ltd T/as Rhino-Rack and may not be used or changed for any other purpose than intended.

2